

# **USB4™ Designated Vendor Specific Extended Capability (DVSEC) for Power Management**

---

Apple Inc.  
HP Inc.  
Intel Corporation  
Microsoft Corporation  
Renesas Corporation  
STMicroelectronics  
Texas Instruments

Version 1.0  
April 2021

Release History

Version	Comments	Issue Date
1.0	First release	April 2021

**NOTE:** Adopters may only use this USB specification to implement USB or third party functionality as expressly described in this Specification; all other uses are prohibited.

**LIMITED COPYRIGHT LICENSE:** The Promoters grant a conditional copyright license under the copyrights embodied in this USB Specification to use and reproduce the Specification for the sole purpose of, and solely to the extent necessary for, evaluating whether to implement the Specification in products that would comply with the specification. Without limiting the foregoing, use of the Specification for the purpose of filing or modifying any patent application to target the Specification or USB compliant products is not authorized. Except for this express copyright license, no other rights or licenses are granted, including without limitation any patent licenses. In order to obtain any additional intellectual property licenses or licensing commitments associated with the Specification a party must execute the USB Adopters Agreement. **NOTE:** By using the Specification, you accept these license terms on your own behalf and, in the case where you are doing this as an employee, on behalf of your employer.

**NOTICE TO USERS:** THE UNIQUE VALUE THAT IS PROVIDED IN THIS SPECIFICATION IS FOR USE IN VENDOR DEFINED MESSAGE FIELDS, DESIGNATED VENDOR SPECIFIC EXTENDED CAPABILITIES, AND ALTERNATE PROTOCOL NEGOTIATION ONLY AND MAY NOT BE USED IN ANY OTHER MANNER, AND A USER OF THE UNIQUE VALUE MAY NOT USE THE UNIQUE VALUE IN A MANNER THAT (A) ALTERS, MODIFIES, HARMS OR DAMAGES THE TECHNICAL FUNCTIONING, SAFETY OR SECURITY OF THE PCI-SIG ECOSYSTEM OR ANY PORTION THEREOF, OR (B) COULD OR WOULD REASONABLY BE DETERMINED TO ALTER, MODIFY, HARM OR DAMAGE THE TECHNICAL FUNCTIONING, SAFETY OR SECURITY OF THE PCI-SIG ECOSYSTEM OR ANY PORTION THEREOF (FOR PURPOSES OF THIS NOTICE, "PCI-SIG ECOSYSTEM" MEANS THE PCI-SIG SPECIFICATIONS, MEMBERS OF PCI-SIG AND THEIR ASSOCIATED PRODUCTS AND SERVICES THAT INCORPORATE ALL OR A PORTION OF A PCI-SIG SPECIFICATION AND EXTENDS TO THOSE PRODUCTS AND SERVICES INTERFACING WITH PCI-SIG MEMBER PRODUCTS AND SERVICES).

#### **INTELLECTUAL PROPERTY DISCLAIMER**

THIS SPECIFICATION IS PROVIDED TO YOU "AS IS" WITH NO WARRANTIES WHATSOEVER INCLUDING ANY WARRANTY OF MERCHANTABILITY, NON-INFRINGEMENT, OR FITNESS FOR ANY PARTICULAR PURPOSE. THE AUTHORS OF THIS SPECIFICATION DISCLAIM ALL LIABILITY FOR INFRINGEMENT OF ANY PROPRIETARY RIGHTS, RELATING TO THE USE OR IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. THE PROVISION OF THIS SPECIFICATION TO YOU DOES NOT PROVIDE YOU WITH ANY LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS.

Please send comments to [techsup@usb.org](mailto:techsup@usb.org).

For industry information, refer to the USB Implementers Forum web page at <http://www.usb.org>.

USB Type-C®, USB-C™, USB 2.0 Type-C™, and USB4™ are trademarks of the Universal Serial Bus Implementers Forum (USB-IF). DisplayPort™ is a trademark of VESA. All product names are trademarks, registered trademarks, or service marks of their respective owners.

Thunderbolt™ is a trademark of Intel Corporation. You may only use the Thunderbolt™ trademark or logo in conjunction with products designed to this specification that complete proper certification and executing a Thunderbolt™ trademark license – see [usb.org/compliance](http://usb.org/compliance) for further information

Copyright © 2021, USB Promoter Group (Apple Inc., HP Inc., Intel Corporation, Microsoft Corporation, Renesas Corporation, STMicroelectronics, and Texas Instruments).

## Contents

1	Preface.....	5
1.1	Scope of Document .....	5
1.2	Related Documents.....	5
1.3	Terms and Abbreviations .....	5
1.4	Documentation Conventions.....	5
1.4.1	Capitalization .....	5
1.4.2	Italic Text.....	5
1.4.3	Numbers and Number Bases.....	5
1.4.4	Bit, Byte, DW, and Symbol Conventions .....	5
1.4.5	Word Usage .....	5
1.4.6	Reserved Values and Fields.....	6
2	Introduction.....	7
3	USB4 DVSEC Header .....	8
4	NHI-Specific Attributes .....	10
5	PCIe-Specific Attributes .....	11
6	USB-Specific Attributes .....	13

## Figures

Figure 2-1.	Example Topology of a USB4 Host Controller with Multiple Host Interfaces .....	7
Figure 3-1.	USB4 DVSEC Header .....	8
Figure 4-1.	NHI-Specific Attributes .....	10
Figure 5-1.	PCIe-Specific Attributes .....	11
Figure 6-1.	USB-Specific Attributes .....	13

## Tables

Table 3-1.	USB4 DVSEC Header Fields .....	8
Table 4-1.	NHI-Specific Attribute Fields .....	10
Table 5-1.	PCIe-Specific Attribute Fields .....	11
Table 6-1.	USB-Specific Attribute Fields .....	13

## 1 Preface

### 1.1 Scope of Document

This document is targeted at USB4 host developers and should be read in conjunction with the Connection Manager Notes in the USB4 Specification and the USB4 Connection Manager Guide.

### 1.2 Related Documents

Universal Serial Bus (USB4™) Specification, Version 1.0 with Errata and ECN through October 15, 2020 (USB4 Specification)

USB4 Connection Manager (CM) Guide, Revision 1.0, [to be published] – (Connection Manager Guide)

PCI Express® Base Specification, Revision 4, Version 1, September 27, 2017 (PCIe Specification)

### 1.3 Terms and Abbreviations

This specification uses the same terms and abbreviations as defined in the USB4 Specification.

### 1.4 Documentation Conventions

#### 1.4.1 Capitalization

Some terms are capitalized to distinguish their definition in the context of this document from their common English meaning. Words not capitalized have their common English meaning.

#### 1.4.2 Italic Text

Italic text is used to identify variable names, register field and packet field names, or reference document titles.

#### 1.4.3 Numbers and Number Bases

Hexadecimal numbers are written with a lower case “h” suffix, e.g. FFFFh and 01h. Hexadecimal numbers larger than four digits are represented with a space dividing each group of four digits, e.g. 1EFF FFFF FFFFh. Binary numbers are written with a lower case “b” suffix, e.g. 1001b and 01b. Binary numbers larger than four digits are written with a space dividing each group of four digits, e.g. 1010 1000 1100b.

All other numbers are decimal.

#### 1.4.4 Bit, Byte, DW, and Symbol Conventions

A bit, byte, DW, or Symbol residing in location *n* within an array is denoted as *bit[n]*, *byte[n]*, *DW[n]*, or *Symbol[n]*.

A sequence of bits, bytes, DWs, or Symbols residing in locations *n* to *m* (inclusive) within an array is denoted as *bit[m:n]*, *byte[m:n]*, *DW[m:n]*, or *Symbol[m:n]*.

#### 1.4.5 Word Usage

The word “shall” is used to indicate mandatory requirements. Mandatory requirements are strictly to be followed in order to conform to this specification and no deviation is permitted.

The phrase “it is recommended” is used to convey that, among several possibilities, one is preferred but not necessarily required.

The word “may” is used to indicate a course of action permissible within the limits of the specification. The word “can” is used only for statements of possibility or capability (i.e. “can” equals “is able to”).

#### **1.4.6 Reserved Values and Fields**

Reserved is a keyword indicating reserved bits, bytes, words, fields, and code values that are set-aside for future standardization. The use and interpretation of these may be specified by future extensions to this specification and, unless otherwise stated, shall not be utilized or adapted by vendor implementation. A reserved bit, byte, word or field shall be set to zero by the sender and shall be ignored by the receiver. Reserved field values shall not be sent by the sender and, if received, shall be ignored by the receiver.


## 2 Introduction

The PCIe specification defines a “Designated Vendor Specific Extended Capability” (DVSEC), which is an extended capability that is used by a vendor to define a configuration register structure that can be implemented by all vendors, while providing a consistent hardware/software interface. This document defines the USB4™ DVSEC registers and is applicable for connection managers that use a PCIe-based host interface.

Platforms with USB4 can have multiple ports requiring multiple instances of USB4 host interfaces. With an Operating System-owned connection manager, there is a load order dependency between the bring up of connection manager and the enumeration of the devices behind the tunneled ports. Specifically, the connection manager will have to load (or resume) first to setup the tunneled paths, followed by the enumeration of devices behind the tunneled ports. The power dependency will have to be maintained during boot up and during exit from low power states.


The USB4 DVSEC helps define a power relation between two or more tunneled ports that do not appear within a tree topology and could be peer devices of the USB4 host interface. USB4 solutions that choose to implement a USB4 DVSEC shall also implement the PCIe Device Serial Number Extended Capability as defined in the PCIe specification and ensure that all PCIe DN bridges and endpoints of the same enclosure return the same Device Serial Number. When possible, the recommendation is to implement the USB4 DVSEC in the DN bridge of the PCIe switch that connects to the relevant endpoint (PCIe/Host Interface/xHCI).

**Figure 2-1. Example Topology of a USB4 Host Controller with Multiple Host Interfaces**



### 3 USB4 DVSEC Header

**Figure 3-1. USB4 DVSEC Header**



**Table 3-1. USB4 DVSEC Header Fields**

Bits	Field	Type	Description
15:0	<i>PCI Express Extended Capability</i>	RO	This field is a PCI-SIG defined ID number that indicates the nature and format of the Extended Capability. Extended Capability ID for the Designated Vendor-Specific Extended Capability is 0023h.
19:16	<i>Cap Version</i>	RO	This field is a PCI-SIG defined version number that indicates the version of the Capability structure present. Shall be 1h for this version of the specification.
31:20	<i>Next Capability Offset</i>	RO	This field contains the offset to the next PCI Express Capability structure or 000h if no other items exist in the linked list of Capabilities. For Extended Capabilities implemented in Configuration Space, this offset is relative to the beginning of PCI-compatible Configuration Space and thus shall always be either 000h (for terminating list of Capabilities) or greater than 0FFh.
47:32	<i>DVSEC Vendor ID</i>	RO	This field is the Vendor ID associated with the vendor that defined the contents of this capability. Shall be 0x8086 (if the vendor intends to use the Intel VID) or 0x1EC0 (if the vendor intends to use the USBIF VID).
51:48	<i>DVSEC Rev</i>	RO	This field is a vendor-defined version number that indicates the version of the DVSEC structure. Software needs to qualify the DVSEC Vendor ID and DVSEC ID before interpreting this field. Shall be 0h.
63:52	<i>DVSEC Length</i>	RO	This field indicates the number of bytes in the entire DVSEC structure, including the PCI Express Extended Capability header, the DVSEC Header 1, DVSEC Header 2, and DVSEC vendor-specific registers.




Bits	Field	Type	Description
			Shall be 10h.
79:64	<i>DVSEC ID</i>	RO	<p>This field is a vendor-defined ID that indicates the nature and format of the DVSEC structure. Software needs to qualify the DVSEC Vendor ID before interpreting this field.</p> <p>Shall be set to 06h if the DVSEC vendor ID field is set to 0x8086. Shall be set to 01h if the DVSEV vendor ID field is set to 0x1EC0.</p>
82:80	<i>Port Type</i>	RO	<p>0x0 - Native Host Interface  0x1 - PCIe Tunneled Port  0x2 - USB Tunneled Port  0x3-0x7 - Reserved</p>
95:83	<i>Reserved</i>	RO	Reserved.
127:96	<i>Port-Specific Attributes</i>	RO	Port specific attributes (see Sections 4, 5, and 6).

#### 4 NHI-Specific Attributes

NHI (Native Host Interface) attributes are applicable for USB4 DVSEC with Port Type = 0x0 (see Table 3-1).

**Figure 4-1. NHI-Specific Attributes**




**Table 4-1. NHI-Specific Attribute Fields**

Bits	Field	Type	Description
2:0	NHI_Instance#	RO	NHI instance number.
31:3	Reserved	RO	Reserved.

## 5 PCIe-Specific Attributes

PCIe attributes are applicable for USB4 DVSEC with Port Type = 0x1 (see Table 3-1). Along with the mapping of the port to the corresponding NHI#, the attributes also provide hints to system software for efficient enumeration of downstream devices.

**Figure 5-1. PCIe-Specific Attributes**



**Table 5-1. PCIe-Specific Attribute Fields**


Bits	Field	Type	Description
2:0	<i>Port_NHI#</i>	RO	Port mapping to NHI instance# 0x0 - 0x6 mapped to NHI# accordingly 0x7 Not mapped to NHI
15:3	<i>Reserved</i>	RO	Reserved.
17:16	<i>Port_Expandability (PE)</i>	RO	0x0: Not implemented 0x1: Non-Expandable port 0x2: Expandable (or daisy chain capable) port with resource requirements that can change at run time. 0x3: Reserved  This field is applicable to root ports or switch downstream ports. This field provides hints to system software to determine if this port is expandable or not. This hint allows the system software to appropriately reserve resources based on the port type.
19:18	<i>Host_Router_Indication (HRI)</i>	RO	00: Not implemented 01: Host - Indicates a port that is physically a part of the host system 10: Reserved 11: Host External facing - indicates a port that is external facing port, accessible to users, of a host system
20:20	<i>D3Cold_Wake_Support (DWS)</i>	RO	0: Not implemented 1: D3Cold wake supported  This field is applicable to root ports or switch downstream ports. This field indicates D3Cold wake support for hierarchy underneath.
23:21	<i>Reserved</i>	RO	Reserved.

Bits	Field	Type	Description
31:24	<i>Bus_Number_Reservation_Hint</i>	RO	0x00: Not implemented 0x01-0xFE: Number of buses required 0xFF: unknown This field is applicable to root ports or switch downstream ports. This hint allows system software to determine number of buses to reserve for the hierarchy underneath.

## 6 USB-Specific Attributes

USB attributes are applicable for USB4 DVSEC with Port Type = 0x2 (see Table 3-1). The number of the xHCI ports may be increased to more than eight by increasing the DVSEC length accordingly.

**Figure 6-1. USB-Specific Attributes**



**Table 6-1. USB-Specific Attribute Fields**

Bits	Field	Type	Description
2:0	Port1_NHI#	RO	Port mapping to NHI instance# 0x0 - 0x6 mapped to NHI# accordingly 0x7 Not mapped to NHI
3:3	<i>Reserved</i>	RO	Reserved.
6:4	Port2_NHI#	RO	Port mapping to NHI instance# 0x0 - 0x6 mapped to NHI# accordingly 0x7 Not mapped to NHI
7:7	<i>Reserved</i>	RO	Reserved.
10:8	Port3_NHI#	RO	Port mapping to NHI instance# 0x0 - 0x6 mapped to NHI# accordingly 0x7 Not mapped to NHI
11:11	<i>Reserved</i>	RO	Reserved.
14:12	Port4_NHI#	RO	Port mapping to NHI instance# 0x0 - 0x6 mapped to NHI# accordingly 0x7 Not mapped to NHI
15:15	<i>Reserved</i>	RO	Reserved.
18:16	Port5_NHI#	RO	Port mapping to NHI instance# 0x0 - 0x6 mapped to NHI# accordingly 0x7 Not mapped to NHI
19:19	<i>Reserved</i>	RO	Reserved.
22:20	Port6_NHI#	RO	Port mapping to NHI instance# 0x0 - 0x6 mapped to NHI# accordingly 0x7 Not mapped to NHI
23:23	<i>Reserved</i>	RO	Reserved.

Bits	Field	Type	Description
26:24	<i>Port7_NHI#</i>	RO	Port mapping to NHI instance# 0x0 - 0x6 mapped to NHI# accordingly 0x7 Not mapped to NHI
27:27	<i>Reserved</i>	RO	Reserved.
30:28	<i>Port8_NHI#</i>	RO	Port mapping to NHI instance# 0x0 - 0x6 mapped to NHI# accordingly 0x7 Not mapped to NHI
31:31	<i>Reserved</i>	RO	Reserved.